















OZNACZENIE		Dz1	Dz2	Dz3	Dz4	Dz5	Dw1
SCHEMAT							
PROPONOWANY WYMIAR MONTAŻOWY	So	2000	2000	1000	1400	2115	1510
	Ho	2800	2100	2800	2100	2800	2065
WYMIARY W ŚWIEŹLE PRZEJŚCIA	Sw	1900	1900	900	1300	2000	1400
	Hw	2700	2000	2000+700	2000	2700	2000
MAX. WYMIAR OŚCIEŻNICY	Sd	2005	2005	1005	1405	2105	1505
	Hd	2790	2090	2790	2090	2790	2050
ILOŚĆ SZTUK	Parter	1	1	3P	1	1	3
	Piętro	-	-	-	-	-	-
	Razem	1	1	3	1	1	3
UWAGI		zewnątrzne, aluminiowe, przeszklone, fragment fasady F5	zewnątrzne, dwuskrzydłowe, równy podział, stalowe, pełne, techniczne	zewnątrzne z naswietłem, aluminiowe	zewnątrzne, dwa skrzydła asymetryczne 90+40, aluminium	zewnątrzne, dwa skrzydła, przeszklone, aluminium	wewnętrzne, dwa skrzydła asymetryczne 90+50

OZNACZENIE		Dw2	Dw3	Dw4	Dw5	Dw6	Dw7	Dw8	Dw9
SCHEMAT									
PROPONOWANY WYMIAR MONTAŻOWY	So	1010	910	1010	1010	1410	1110	910	1510
	Ho	2065	2065	2065	2065	2065	2065	2065	2065
WYMIARY W ŚWIETLE PRZEJŚCIA	Sw	900	800	900	900	1300	1000	900	1400
	Hw	2000	2000	2000	2000	2000	2000	2000	2000
MAX. WYMIAR OŚCIEŻNICY	Sd	1005	905	1005	1005	1405	1105	905	1505
	Hd	2050	2050	2050	2050	2050	2050	2050	2050
ILOŚĆ SZTUK	Parter	2L+4P	2L	5P	2L+1P	1	-	-	-
	Piętro	1L+1P	-	1L+2P	2L	-	1P	1	1
	Razem	8	2	8	5	1	1	1	1
UWAGI				z samozamykaczem		dymoszczelne	z samozamykaczem	przesuwne	